


HARDWOOD FLOORING



TECHNICAL DETAILS

Notes:

Pattern: Herringbone



Color: Alps

PRODUCT INFO		PACKAGING		STRUCTURE
Species	White European Oak	BOX 15 kg (33 lb) 1,318 m ² (14 ft ²) 125 mm (5") 280 mm (11") 615 mm (2')	84,352 m ² (908 ft ²) 945 kg (2083 lb) 1100 mm (3,6') 1150 mm (3,8') 1230 mm (4')	2-layer Engineered Construction * Solid wood 4 mm ** Plywood *** * High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood
Finish	UV Silk			
Structure	Engineered (2-layer)			
Joint	T&G			
Bevel	Micro (0,5 mm)			
Surface	Light Brush	PALLET		
Grade	Select			
DIMENSIONS				
Thickness	15 mm (5/8")			
Width	90 mm (3,55")			
Row Length	610 mm (23,6')			
Angle	90			

FINISH		DESCRIPTION			
Sheen \ Gloss	Matte	natural wood	rare knots		
Look	Semi-open pores, wire brushed	even texture	perfect look		
Feeling	Transfer warmth of natural wood	uniform	slight color variation		
Type	UV cured modified polyurethane-acrylate	clean planks	minimal sapwood		
Wear resistance	High	smooth surface	selected grain		
Scratch resistance	Medium	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.			
Slip resistance	50 (SRV dry)				
Resistance to chemical agents	Class 5 (Except blue ink)				
Maintenance	Maintenance free				
Repairability	Easy				
TECHNICAL INFORMATION					
Characteristics (EN 14342)				Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF			Deviation on Thickness	0,2 mm
Pentachlorophenol content	None			Deviation on Width	0,2 mm
Thermal resistance	0,118 m ² K/W			Height Difference	0,2 mm
Thermal conductivity	0,161 W/(m K)			Cup	<0,2% of width
Fire resistance	Dfl-s1			Bow	<0,5% of length
		Spring	<0,1% of length		

PRODUCT USE

INSTALLATION	STORAGE & USE
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.</p>	<p>Air Humidity 40-65% Temperature +18°C ... +22°C (64°F ... 72°F)</p>
CARE & MAINTENANCE	DESCRIPTIONS & IMAGERY
<p>Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.</p>	<p>Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.</p>

