

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Alps

Layout:



Pattern: Herringbone

1. PRODUCT INFO		2. STRUCTURE	3. PACKAGING	
Species	White European Oak	2-layer Engineered Construction * Solid wood 4 mm ** Plywood or Soft Wood + Plywood*** * High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood or QR softwood stabilizing bars with compensation gaps & plywood reinforcements on the end tenon side		
Finish	UV Silk		BOX	PALLET
Structure	Engineered (2-layer)		1,296 m ² (14 ft ²)	82,944 m ² (893 ft ²)
Joint	T&G		Dimensions (TWL): 125 x 280 x 605 mm (5"*11"*2')	Dimensions (LWH): 1230 x 1150 x 1100 mm (4'*3,8'*3,6')
Bevel	4-sides		Weight: 15 kg (33 lb)	Weight: 929 kg (2048 lb)
Surface	Light Brush	5. DESCRIPTION Name: Select Color variation: Knots: Other: Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.		
Grade	Select			
DIMENSIONS				
Thickness	15 mm (5/8")			
Width	90 mm (3,55")			
Row Length	600 mm (1,97')			
Angle	90			
4. FINISH		5. DESCRIPTION		
Sheen \ Gloss	Matte	Name	Select	
Look	Semi-open pores, wire brushed	Color variation		
Feeling	Transfer warmth of natural wood	Knots		
Type	UV cured modified polyurethane-acrylate	Other		
Wear resistance	High	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.		
Scratch resistance	Medium			
Slip resistance	50 (SRV dry)			
Resistance to chemical agents	Class 5 (Except blue ink)			
Maintenance	Maintenance free			
Repairability	Easy			
6. TECHNICAL INFORMATION				
Characteristics (EN 14342)		Deviations (EN 13489)		
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm	
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm	
Thermal resistance (m ² K/W)	0,118/0,104	Height Difference	+/- 0,2 mm	
Thermal conductivity (W/(m K))	0,161/0,144	Cup	<0,2% of width	
Fire resistance	Dfl-s1	Bow	<0,5% of length	
		Spring	<0,1% of length	

PRODUCT USE

7. INSTALLATION	8. STORAGE & USE
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.</p>	<p>Air Humidity 40-65%</p> <p>Temperature +18°C ... +22°C (64°F ... 72°F)</p>
9. CARE & MAINTENANCE	10. DESCRIPTIONS & IMAGERY
<p>Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.</p>	<p>Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.</p>

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
 Ruunaoja tn 3, 11415, Tallinn, Estonia
 VAT EE102590311
 E-mail: info@me-floor.com
 www.me-floor.com
 Inst.: @me_floor_



NO ADDED formaldehyde

