


HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Autumn Leaf

Layout:




Pattern: Herringbone

1. PRODUCT INFO

Species	White European Oak
Finish	UV Silk
Structure	Engineered (2-layer)
Joint	T&G
Bevel	4-sides
Surface	Light Brush
Grade	Nature
DIMENSIONS	
Thickness	15 mm (5/8")
Width	90 mm (3,55")
Side Length	600 mm (1,97')
Angle	90°

2. STRUCTURE

2-layer Engineered Construction *



Solid wood 4 mm **
Plywood or
Soft Wood + Plywood***
* High Balance and Stability
** Saw Cut White European Oak
*** Birch water resistant plywood or
QR softwood stabilizing bars with
compensation gaps & plywood
reinforcements on the end tenon side

3. PACKAGING

BOX	PALLET
1,296 m2 (14 ft2)	82,944 m2 (893 ft2)
Dimensions (TWL): 125 x 280 x 605 mm (5"*11"*2')	Dimensions (LWH): 1230 x 1150 x 1100 mm (4'*3,8'*3,6')
Weight: 15 kg (33 lb)	Weight: 929 kg (2048 lb)

4. FINISH

Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	UV cured modified polyurethane-acrylate
Wear resistance	High
Scratch resistance	Medium
Slip resistance	50 (SRV dry)
Resistance to chemical agents	Class 5 (Except blue ink)
Maintenance	Maintenance free
Repairability	Easy

5. DESCRIPTION

Name	Nature
Color variation	
Knots	
Other	
Nature grade looks pretty clean and organic. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.	

6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance (m2 K/W)	0,118/0,104	Deviation on Length	+/- 0,3 mm
Thermal conductivity (W/(m K))	0,161/0,144	Height Difference	+/- 0,2 mm
Fire resistance	Dfl-s1	Cup	<0,2% of width
		Bow	<0,5% of length
		Spring	<0,1% of length


PRODUCT USE

7. INSTALLATION




Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.

8. STORAGE & USE



Air Humidity
40-65%



Temperature
+18°C ... +22°C
(64°F ... 72°F)

9. CARE & MAINTENANCE

Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Ruunaoja tn 3, 11415, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: @me_floor_



NO ADDED
formaldehyde

