

# HARDWOOD FLOORING

## TECHNICAL DETAILS



Color: Bourbon. Bespoke

Layout:




Pattern: Plank

### 1. PRODUCT INFO

|            |                         |
|------------|-------------------------|
| Species    | White European Oak      |
| Finish     | Silk Oxi                |
| Structure  | Engineered (2-layer)    |
| Joint      | T&G                     |
| Bevel      | 1,5 mm (long side only) |
| Surface    | Deep Brush              |
| Grade      | Character               |
| DIMENSIONS |                         |
| Thickness  | 15,5 mm                 |
| Width      | 220 mm                  |
| Row Length | 2200 mm                 |
| Shorts     | 25%                     |

### 2. STRUCTURE

2-layer Engineered Construction \*



\* High Balance and Stability

\*\* Saw Cut White European Oak

\*\*\* Birch water resistant plywood

### 3. PACKAGING

|   |  |
|---|--|
|   |  |
| BOX                                     | PALLET                                     |
| 1,936 m2 (21 ft2)                       | 106,48 m2 (1146 ft2)                       |
| Dimensions (TWL):<br>65 x 222 x 2220 mm | Dimensions (LWH):<br>2300 x 1100 x 1120 mm |
| Weight:<br>25 kg (55 lb)                | Weight:<br>1403 kg (3093 lb)               |

### 4. FINISH

|                               |                                      |
|-------------------------------|--------------------------------------|
| Sheen \ Gloss                 | Matte                                |
| Look                          | Semi-open pores, wire brushed        |
| Feeling                       | Transfer warmth of natural wood      |
| Type                          | Hardwax oil                          |
| Wear resistance               | Low                                  |
| Scratch resistance            | Low                                  |
| Slip resistance               | 50 (SRV dry)                         |
| Resistance to chemical agents | DIN68861 - Class A1 (no water spots) |
| Maintenance                   | Maintenance easy                     |
| Repairability                 | Easy                                 |

### 5. DESCRIPTION

|                 |           |
|-----------------|-----------|
| Name            | Character |
| Color variation |           |
| Knots           |           |
| Other           |           |


Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections in the face work (torn grain) to design advantage.

### 6. TECHNICAL INFORMATION

|                             |                |                        |                 |
|-----------------------------|----------------|------------------------|-----------------|
| Characteristics (EN 14342)  |                | Deviations (EN 13489)  |                 |
| Formaldehyde emission class | E1; ULEF       | Deviation on Thickness | +/- 0,2 mm      |
| Pentachlorophenol content   | None           | Deviation on Width     | +/- 0,2 mm      |
| Thermal resistance          | 0,118 m2 K\W   | Height Difference      | +/- 0,2 mm      |
| Thermal conductivity        | 0,161 W\ (m K) | Cup                    | <0,2% of width  |
| Fire resistance             | Dfl-s1         | Bow                    | <0,5% of length |
|                             |                | Spring                 | <0,1% of length |


## PRODUCT USE

### 7. INSTALLATION




Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Semifloating installation as well.  
Applicable above, on and below ground level.  
Suitable for underfloor heating.

### 8. STORAGE & USE



Air Humidity  
40-65%



Temperature  
+18°C ... +22°C  
(64°F ... 72°F)

### 9. CARE & MAINTENANCE

Maintenance of hardwood floors with Silk Oxi assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.

### 10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.



ME Decor Group OÜ  
Kopli 27, 10412, Tallinn, Estonia  
VAT EE102590311  
E-mail: [info@me-decor.com](mailto:info@me-decor.com)  
[www.me-floor.com](http://www.me-floor.com)  
Inst.: @me\_floor\_

