


# HARDWOOD FLOORING

## TECHNICAL DETAILS

Notes:

Pattern: Herringbone



Color: Brown

### PRODUCT INFO


Species	White European Oak
Finish	UV Silk
Structure	Engineered (2-layer)
Joint	T&G
Bevel	Micro (0,5 mm)
Surface	Light Brush
Grade	Character
<b>DIMENSIONS</b>	
Thickness	15 mm (5/8")
Width	125 mm (5")
Row Length	600 mm (23,6')
Angle	90

### PACKAGING

<b>BOX</b>	13 kg (30 lb)	1,2 m <sup>2</sup> (13 ft <sup>2</sup> )
	125 mm (5")	260 mm (10,25')
<b>PALLET</b>	860 kg (1896 lb)	76,8 m <sup>2</sup> (827 ft <sup>2</sup> )
	1100 mm (3,6')	1230 mm (4')
	1070 mm (3,5')	

### STRUCTURE

2-layer Engineered Construction \*



\* High Balance and Stability  
 \*\* Saw Cut White European Oak  
 \*\*\* Birch water resistant plywood

### FINISH

Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	UV cured modified polyurethane-acrylate
Wear resistance	High
Scratch resistance	Medium
Slip resistance	50 (SRV dry)
Resistance to chemical agents	Class 5 (Except blue ink)
Maintenance	Maintenance free
Repairability	Easy

### DESCRIPTION

antique wood	worm holes
authentic natural	oak texture
diverse color	variation
sapwood	unlimited burls
brown streaks	tight knots

Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections in the face work (torn grain) to design advantage.

### TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m <sup>2</sup> K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length


## PRODUCT USE

### INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.  
 Applicable above, on and below ground level.  
 Suitable for underfloor heating.

### STORAGE & USE



Air Humidity 40-65%  
 Temperature +18°C ... +22°C (64°F ... 72°F)

### CARE & MAINTENANCE

Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with oil.

### DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.