

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Natural

Layout:


Pattern: Castle

1. PRODUCT INFO

Species	White European Oak
Finish	Unfinished
Structure	Engineered (2-layer)
Joint	T&G
Bevel	Micro
Surface	Sanded
Grade	Nature
DIMENSIONS	
Thickness	15 mm (5/8")
Width	1000 mm (3,28')
Row Length	1000 mm (3,28')

2. STRUCTURE

2-layer Engineered Construction *



* High Balance and Stability
 ** Saw Cut White European Oak
 *** Birch water resistant plywood

3. PACKAGING

BOX	PALLET
2 m ² (21,53 ft ²)	64 m ² (689 ft ²)
Dimensions (TWL): 30 x 1010 x 1010 mm (2,36"*2,66"*2,66')	Dimensions (LWH): 1010 x 1010 x 970 mm (5,31"*2,66"*3,18')
Weight: 23 kg (51 lb)	Weight: 736 kg (1623 lb)

4. FINISH


Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	Unfinished
Wear resistance	n/a
Scratch resistance	n/a
Slip resistance	n/a
Resistance to chemical agents	n/a
Maintanance	n/a
Repairability	Easy

5. DESCRIPTION

Name	Nature
Color variation	
Knots	
Other	
Nature grade looks pretty clean. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots. Slight imperfections in face work (torn grain) and burns are admitted.	


6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length



PRODUCT USE

7. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.

8. STORAGE & USE

Air Humidity 40-65%	Temperature +18°C ... +22°C (64°F ... 72°F)

9. CARE & MAINTANENCE

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
 Ruunaoja tn 3, 11415, Tallinn, Estonia
 VAT EE102590311
 E-mail: info@me-decor.com
 www.me-floor.com
 Inst.: @me_floor_



NO ADDED formaldehyde

