

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Classic

Layout:




Pattern: Chevron

1. PRODUCT INFO

Species	White European Oak
Finish	UV Silk
Structure	Engineered (2-layer)
Joint	T&G
Bevel	Micro (0,5 mm)
Surface	Light Brush
Grade	Select
DIMENSIONS	
Thickness	15 mm (5/8")
Width	90 mm (3,54")
Row Length	510 mm (1,67')
Angle	45

2. STRUCTURE

2-layer Engineered Construction *



Solid wood 4 mm **
Plywood ***
* High Balance and Stability
** Saw Cut White European Oak
*** Birch water resistant plywood

3. PACKAGING

BOX	PALLET
1,1016 m2 (12 ft2)	70,502 m2 (760 ft2)
Dimensions (TWL): 125 x 280 x 615 mm (5"*11"*2')	Dimensions (LWH): 1260 x 1150 x 1100 mm (4,15'*3,8'*3,6')
Weight: 12 kg (27 lb)	Weight: 790 kg (1741 lb)

4. FINISH

Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	UV cured modified polyurethane-acrylate
Wear resistance	High
Scratch resistance	Medium
Slip resistance	50 (SRV dry)
Resistance to chemical agents	Class 5 (Except blue ink)
Maintenance	Maintenance free
Repairability	Easy

5. DESCRIPTION

Name	Select
Color variation	
Knots	
Other	

Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.


6. TECHNICAL INFORMATION

Characteristics (EN 14342)	Deviations (EN 13489)
Formaldehyde emission class	E1; ULEF
Pentachlorophenol content	None
Thermal resistance	0,118 m2 K\W
Thermal conductivity	0,161 W\ (m K)
Fire resistance	Dfl-s1
	Deviation on Thickness
	+/- 0,2 mm
	Deviation on Width
	+/- 0,2 mm
	Height Difference
	+/- 0,2 mm
	Cup
	<0,2% of width
	Bow
	<0,5% of length
	Spring
	<0,1% of length



PRODUCT USE

7. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above, on and below ground level.
Suitable for underfloor heating.

8. STORAGE & USE



Air Humidity
40-65%



Temperature
+18°C ... +22°C
(64°F ... 72°F)

9. CARE & MAINTENANCE

Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.



ME Decor Group OÜ
Kopli 27, 10412, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: @me_floor_



nwfa
compliant

NO ADDED
formaldehyde

