

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Grey	Layout:	Pattern: Plank
-------------	---------	----------------

1. PRODUCT INFO 2. STRUCTURE 3. PACKAGING

Species	White European Oak	2-layer Engineered Construction * * High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood	 BOX 2,736m ² (29 ft ²)/mixed Dimensions (TWL): 125x200x1915 mm/mixed (5'*7,9'*6,3')/mixed Weight: 31 kg (68 lb)/mixed	 PALLET 109,44 m ² (1178 ft ²)/mixed Dimensions (LWH): 1930x1030x1050 mm/mixed (6,4'*3,4'*3,45')/mixed Weight: 1226 kg (2702 lb)/mixed
Finish	UV Silk			
Structure	Engineered (2-layer)			
Joint	T&G			
Bevel	4-sides			
Surface	Light Brush			
Grade	Character			
DIMENSIONS				
Thickness	15 mm (5/8")			
Width	180 mm (7,1")			
Row Length	*1900/**2400 mm (6,25'/7,87')			
Shorts	*25%/**(70%-1600-2400;30%-600-1600)			

4. FINISH 5. DESCRIPTION

Sheen \ Gloss	Matte	Name	Character
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	UV cured modified polyurethane-acrylate	Other	
Wear resistance	High	Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections in the face work (torn grain) to design advantage.	
Scratch resistance	Medium		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	Class 5 (Except blue ink)		
Maintenance	Maintanance free		
Repairability	Easy		

6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

PRODUCT USE

7. INSTALLATION 8. STORAGE & USE

 Level Floor Heating Glue-down Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Semifloating installation as well. Applicable above, on and below ground level. Suitable for underfloor heating.	 Air Humidity 40-65%	 Temperature +18°C ... +22°C (64°F ... 72°F)
--	----------------------------	---

9. CARE & MAINTENANCE 10. DESCRIPTIONS & IMAGERY

Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. Should be periodically renewed with oil.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.
--	---

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
 Ruunaoja tn 3, 11415, Tallinn, Estonia
 VAT EE102590311
 E-mail: info@me-decor.com
 www.me-floor.com
 Inst.: @me_floor_



NO ADDED formaldehyde

