

# HARDWOOD FLOORING

## TECHNICAL DETAILS



Color: Natural	Layout:	Pattern: Louvre
----------------	---------	-----------------

1. PRODUCT INFO		2. STRUCTURE	3. PACKAGING	
Species	White European Oak	2-layer Engineered Construction *  Solid wood 4 mm ** Plywood *** 		
Finish	Silk Oxi		BOX	PALLET
Structure	Engineered (2-layer)	* High Balance and Stability	1,28 m2 (10,76 ft2)	30,72 m2 (323ft2)
Joint	T&G	** Saw Cut White European Oak	Dimensions (TWL):	Dimensions (LWH):
Bevel	Micro (0,5 mm)	*** Birch water resistant plywood	120 x 405 x 405 mm	810 x 810 x 730 mm
Surface	Light Brush		(4,72'*1,33'*1,33')	(2,66'*2,66'*2,4')
Grade	Select		Weight:	Weight:
DIMENSIONS			15 kg (33,1 lb)	370 kg (816 lb)
Thickness	15 mm (5/8")			
Width	400 mm (1,31')			
Row Length	400 mm (1,31')			
Shorts	-			

4. FINISH		5. DESCRIPTION	
Sheen \ Gloss	Matte	Name	Select
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	Hardwax oil	Other	
Wear resistance	Low	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood. 	
Scratch resistance	Low		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	DIN68861 - Class A1 (no water spots)		
Maintanance	Easy		
Repairability	Easy		

6. TECHNICAL INFORMATION			
Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m2 K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

## PRODUCT USE

7. INSTALLATION	8. STORAGE & USE
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.</p>	<p>Air Humidity 40-65%</p> <p>Temperature +18°C ... +22°C (64°F ... 72°F)</p>

9. CARE & MAINTENANCE	10. DESCRIPTIONS & IMAGERY
Maintenance of hardwood floors with Silk Oxi assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with hardwax oil.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.