

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Natural Unfinished

Layout:



Pattern: Chevron

1. PRODUCT INFO

Species	White European Oak
Finish	Unfinished
Structure	Engineered (2-layer)
Joint	T&G
Bevel	Micro (0,5 mm)
Surface	Sanded (120 grit)
Grade	Select
DIMENSIONS	
Thickness	15 mm (5/8")
Width	90 mm (3,54")
Row Length	610 mm (2')
Angle	45°

2. STRUCTURE

2-layer Engineered Construction *

Solid wood 4 mm **
Plywood ***



* High Balance and Stability
** Saw Cut White European Oak
*** Birch water resistant plywood

3. PACKAGING

BOX	PALLET
1,318 m2 (14 ft2)	84,352 m2 (908 ft2)
Dimensions (TWL): 125 x 280 x 715 mm (5"*11"*2')	Dimensions (LWH): 1260 x 1150 x 1100 mm (4,15'*3,8'*3,6')
Weight: 15 kg (33 lb)	Weight: 944 kg (2082 lb)

4. FINISH

Sheen \ Gloss	n/a
Look	Smooth
Feeling	Transfer warmth of natural wood
Type	Unfinished
Wear resistance	n/a
Scratch resistance	n/a
Slip resistance	n/a
Resistance to chemical agents	n/a
Maintanance	n/a
Repairability	Easy

5. DESCRIPTION

Name	Select
Color variation	
Knots	
Other	

Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.


6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m2 K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length



PRODUCT USE

7. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above, on and below ground level.
Suitable for underfloor heating.

8. STORAGE & USE

Air Humidity 40-65%	Temperature +18°C ... +22°C (64°F ... 72°F)

9. CARE & MAINTENANCE

Maintenance of hardwood floors depends on applied finish and assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Ruunaoja tn 3, 11415, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: @me_floor_



NO ADDED formaldehyde

