

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Sepia

Layout:




Pattern: Plank

1. PRODUCT INFO

| | |
|-------------------|----------------------|
| Species | White European Oak |
| Finish | UV Silk |
| Structure | Engineered (2-layer) |
| Joint | T&G |
| Bevel | Micro (0,5 mm) |
| Surface | Light Brush |
| Grade | Character |
| DIMENSIONS | |
| Thickness | 15 mm (5/8") |
| Width | 190 mm (7,5") |
| Row Length | 1900 mm (6,25') |
| Shorts | 25% |

2. STRUCTURE



2-layer Engineered Construction *

Solid wood 4 mm **

Plywood ***

* High Balance and Stability

** Saw Cut White European Oak

*** Birch water resistant plywood

3. PACKAGING

| | |
|--|---|
| | |
| BOX | PALLET |
| 2,888 m ² (31 ft ²) | 115,52 m ² (1243 ft ²) |
| Dimensions (TWL): 125 x 200 x 1915 mm (5"*7,9"*6,3') | Dimensions (LWH): 1930 x 1030 x 1050 mm (6,4'*3,4'*3,45') |
| Weight: 32 kg (71 lb) | Weight: 1294 kg (2852 lb) |

4. FINISH

| | |
|-------------------------------|---|
| Sheen \ Gloss | Matte |
| Look | Semi-open pores, wire brushed |
| Feeling | Transfer warmth of natural wood |
| Type | UV cured modified polyurethane-acrylate |
| Wear resistance | High |
| Scratch resistance | Medium |
| Slip resistance | 50 (SRV dry) |
| Resistance to chemical agents | Class 5 (Except blue ink) |
| Maintanance | Maintanance free |
| Repairability | Easy |

5. DESCRIPTION

| | |
|-----------------|-----------|
| Name | Character |
| Color variation | |
| Knots | |
| Other | |


Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections in the face work (torn grain) to design advantage.

6. TECHNICAL INFORMATION

| | | | |
|-----------------------------|--------------------------|------------------------|-----------------|
| Characteristics (EN 14342) | | Deviations (EN 13489) | |
| Formaldehyde emission class | E1; ULEF | Deviation on Thickness | 0,2 mm |
| Pentachlorophenol content | None | Deviation on Width | 0,2 mm |
| Thermal resistance | 0,118 m ² K\W | Height Difference | 0,2 mm |
| Thermal conductivity | 0,161 W\ (m K) | Cup | <0,2% of width |
| Fire resistance | Dfl-s1 | Bow | <0,5% of length |
| | | Spring | <0,1% of length |

PRODUCT USE

7. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Semifloating installation as well.

Applicable above, on and below ground level.

Suitable for underfloor heating.

8. STORAGE & USE

| | |
|------------------------|---|
| | |
| Air Humidity 40-65% | Temperature +18°C ... +22°C (64°F ... 72°F) |

9. CARE & MAINTENANCE

Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. Should be periodically renewed with oil.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.



ME Decor Group OÜ
Kopli 27, 10412, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: @me_floor_



nwfa
compliant

NO ADDED
formaldehyde

