

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Sepia	Layout:	Pattern: Chevron
--------------	---------	------------------

1. PRODUCT INFO		2. STRUCTURE	3. PACKAGING									
Species	White European Oak	2-layer Engineered Construction *		<table border="1"> <tr> <th>BOX</th> <th>PALLET</th> </tr> <tr> <td>1,2 m² (13 ft²)</td> <td>76,8 m² (827 ft²)</td> </tr> <tr> <td>Dimensions (TWL): 125 x 260 x 740 mm (5"*10,25"*2,45')</td> <td>Dimensions (LWH): 1510 x 1070x 1100 mm (4,95'*3,5'*3,6')</td> </tr> <tr> <td>Weight: 13 kg (30 lb)</td> <td>Weight: 860 kg (1896 lb)</td> </tr> </table>	BOX	PALLET	1,2 m ² (13 ft ²)	76,8 m ² (827 ft ²)	Dimensions (TWL): 125 x 260 x 740 mm (5"*10,25"*2,45')	Dimensions (LWH): 1510 x 1070x 1100 mm (4,95'*3,5'*3,6')	Weight: 13 kg (30 lb)	Weight: 860 kg (1896 lb)
BOX	PALLET											
1,2 m ² (13 ft ²)	76,8 m ² (827 ft ²)											
Dimensions (TWL): 125 x 260 x 740 mm (5"*10,25"*2,45')	Dimensions (LWH): 1510 x 1070x 1100 mm (4,95'*3,5'*3,6')											
Weight: 13 kg (30 lb)	Weight: 860 kg (1896 lb)											
Finish	UV Silk	Solid wood 4 mm **										
Structure	Engineered (2-layer)	Plywood ***										
Joint	T&G											
Bevel	Micro (0,5 mm)											
Surface	Light Brush											
Grade	Select											
DIMENSIONS		* High Balance and Stability										
Thickness	15 mm (5/8")	** Saw Cut White European Oak										
Width	125 mm (5")	*** Birch water resistant plywood										
Row Length	600 mm (1,97')											
Angle	60											

4. FINISH		5. DESCRIPTION	
Sheen \ Gloss	Matte	Name	Select
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	UV cured modified polyurethane-acrylate	Other	
Wear resistance	High	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.	
Scratch resistance	Medium		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	Class 5 (Except blue ink)		
Maintanance	Maintenance free		
Repairability	Easy		

6. TECHNICAL INFORMATION			
Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

PRODUCT USE

7. INSTALLATION	8. STORAGE & USE
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.</p>	<p>Air Humidity 40-65%</p> <p>Temperature +18°C ... +22°C (64°F ... 72°F)</p>

9. CARE & MAINTENANCE	10. DESCRIPTIONS & IMAGERY
Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

