

# HARDWOOD FLOORING

## TECHNICAL DETAILS



Color: Natural

Layout:



Pattern: Smart Herringbone

1. PRODUCT INFO		2. STRUCTURE		3. PACKAGING									
Species	White European Oak	2-layer Engineered Construction											
Finish	UV Lacquer Matt												
Structure	Engineered (2-layer)			<table border="1"> <thead> <tr> <th>BOX</th> <th>PALLET</th> </tr> </thead> <tbody> <tr> <td>2,63 m<sup>2</sup> (28 ft<sup>2</sup>)</td> <td>94,68 m<sup>2</sup> (1019 ft<sup>2</sup>)</td> </tr> <tr> <td>Dimensions (T<sub>W</sub>L): 200 x 280 x 475 mm (7,87''*11''*1,56')</td> <td>Dimensions (L<sub>W</sub>H): 950 x 840 x 1200 mm (3,12'*2,76'*3,94')</td> </tr> <tr> <td>Weight: 15 kg (33 lb)</td> <td>Weight: 540 kg (1190 lb)</td> </tr> </tbody> </table>		BOX	PALLET	2,63 m <sup>2</sup> (28 ft <sup>2</sup> )	94,68 m <sup>2</sup> (1019 ft <sup>2</sup> )	Dimensions (T <sub>W</sub> L): 200 x 280 x 475 mm (7,87''*11''*1,56')	Dimensions (L <sub>W</sub> H): 950 x 840 x 1200 mm (3,12'*2,76'*3,94')	Weight: 15 kg (33 lb)	Weight: 540 kg (1190 lb)
BOX	PALLET												
2,63 m <sup>2</sup> (28 ft <sup>2</sup> )	94,68 m <sup>2</sup> (1019 ft <sup>2</sup> )												
Dimensions (T <sub>W</sub> L): 200 x 280 x 475 mm (7,87''*11''*1,56')	Dimensions (L <sub>W</sub> H): 950 x 840 x 1200 mm (3,12'*2,76'*3,94')												
Weight: 15 kg (33 lb)	Weight: 540 kg (1190 lb)												
Joint	T&G	<p>Solid wood 3,5 mm *</p> <p>Soft Wood **</p>											
Bevel	No Bevel	<p>* Saw Cut White European Oak Lamella nominal value variations are normal due to the specific nature of wood and each decor and not considered defects</p>											
Surface	Smooth	<p>** Base Softwood stabilizing bars with compensation gaps</p>											
Grade	Rustic												
DIMENSIONS													
Thickness	10 mm (3/8")												
Width	70 mm (2,76")												
Row Length	470 mm (1,55')												
Angle	90												
4. FINISH		5. DESCRIPTION											
Sheen \ Gloss	Matte	Name	Rustic										
Look	Closed pores, smooth	Color variation											
Feeling	Transfer warmth of natural wood	Knots											
Type	UV cured modified polyurethane-acrylate	Other											
Wear resistance	High	<p>Rustic Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections in the face work (torn grain) to design</p>											
Scratch resistance	Medium												
Slip resistance	50 (SRV dry)												
Resistance to chemical agents	Class 5 (Except blue ink)												
Maintanance	Maintenance free												
Repairability	Easy												
6. TECHNICAL INFORMATION													
Characteristics (EN 14342)						Deviations (EN 13489)							
Formaldehyde emission class	E1; ULEF					Deviation on Thickness	+/- 0,2 mm						
Pentachlorophenol content	None					Deviation on Width	+/- 0,2 mm						
Thermal resistance	0,08 m <sup>2</sup> K\W					Height Difference	+/- 0,2 mm						
Thermal conductivity	0,13 W\ (m K)					Cup	<0,2% of width						
Fire resistance	Dfl-s1	Bow	<0,5% of length										
		Spring	<0,1% of length										

## PRODUCT USE

7. INSTALLATION		8. STORAGE & USE	
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.</p>		<p>Air Humidity 40-65%</p> <p>Temperature +18°C ... +22°C (64°F ... 72°F)</p>	
9. CARE & MAINTENANCE		10. DESCRIPTIONS & IMAGERY	
<p>Maintenance of hardwood floors with UV Lacquer Matt assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed.</p>		<p>Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.</p>	

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ  
Ruunaoja tn 3, 11415, Tallinn, Estonia  
VAT EE102590311  
E-mail: info@me-decor.com  
www.me-floor.com  
Inst.: @me\_floor\_



NO ADDED formaldehyde

