

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Natural

Layout:




1. PRODUCT INFO

Species	White European Oak
Finish	UV Oil Matt
Structure	Engineered (3-layer)
Joint	Click
Bevel	Micro (4-sides)
Surface	Light Brush
Grade	Rustic
DIMENSIONS	
Thickness	14 mm (9/16")
Width	164 mm (6,45")
Row Length	2230 mm (7,32')
Shorts	30%

2. STRUCTURE

3-layer Engineered Construction *



Solid wood 3.5 mm **
Softwood
Softwood

* Saw Cut White European Oak
Lamella nominal value variations are normal due to the specific nature of wood and each decor and not considered defects

** Core & Base
QR Softwood stabilizing bars with compensation gaps & plywood reinforcements on the short sides on soft stabilising foundation

3. PACKAGING

BOX	PALLET
2,56 m ² (27,6 ft ²)	107,52 m ² (1158 ft ²)
Dimensions (TWL): 100 x 166 x 2235 mm (3,94"*6,54"*7,33')	Dimensions (LWH): 2235 x 1000 x 700 mm (7,33'*3,28'*2,3')
Weight: 19,3 kg (64 lb)	Weight: 810 kg (2657 lb)

4. FINISH

Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	UV cured modified polyurethane-acrylate
Wear resistance	Medium
Scratch resistance	Medium
Slip resistance	50 (SRV dry)
Resistance to chemical agents	Class 4
Maintenance	Maintenance free
Repairability	Easy

5. DESCRIPTION

Name	Rustic
Color variation	
Knots	
Other	


6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,104 m ² K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,14 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length



PRODUCT USE

7. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Floating installation as well.
Applicable above, on and below ground level.
Suitable for underfloor heating.

8. STORAGE & USE

Air Humidity 40-65%	Temperature +18°C ... +22°C (64°F ... 72°F)

9. CARE & MAINTENANCE

Maintenance of hardwood floors with UV Oil Matt assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Ruunaoja tn 3, 11415, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-floor.com
www.me-floor.com
Inst.: @me_floor_



NO ADDED formaldehyde

