

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Natural

Layout:




Pattern: Tower

1. PRODUCT INFO

Species	White European Oak
Finish	Silk Oxi
Structure	Engineered (2-layer)
Joint	T&G
Bevel	4-sides
Surface	Light Brush
Grade	Nature
DIMENSIONS	
Thickness	15 mm (5/8")
Width	800 mm (2,62')
Row Length	800 mm (2,62')
Shorts	-

2. STRUCTURE

2-layer Engineered Construction *



* High Balance and Stability
** Saw Cut White European Oak
*** Birch water resistant plywood

3. PACKAGING

BOX	PALLET
2,56 m ² (28 ft ²)	81,92 m ² (882 ft ²)
Dimensions (TWL): 60 x 810 x 810 mm (2,36"*2,66'*2,66')	Dimensions (LWH): 1620 x 810 x 970 mm (5,31'*2,66'*3,18')
Weight: 30 kg (67 lb)	Weight: 960 kg (2117 lb)

4. FINISH

Sheen \ Gloss	Matte
Look	Semi-open pores, wire brushed
Feeling	Transfer warmth of natural wood
Type	UV cured modified polyurethane-acrylate
Wear resistance	Low
Scratch resistance	Low
Slip resistance	50 (SRV dry)
Resistance to chemical agents	DIN68861 - Class A1 (no water spots)
Maintanance	Easy
Repairability	Easy

5. DESCRIPTION

Name	Nature
Color variation	
Knots	
Other	

Nature grade looks pretty clean. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots. Slight imperfections in face work (torn grain) and burns are admitted.



6. TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

PRODUCT USE

7. INSTALLATION




Level




Glue-down

Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above, on and below ground level.

8. STORAGE & USE



Air Humidity
40-65%



Temperature
+18°C ... +22°C
(64°F ... 72°F)

9. CARE & MAINTENANCE

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with.

10. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Ruunaoja tn 3, 11415, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: [@me_floor_](https://www.instagram.com/me_floor_)

