

HARDWOOD FLOORING

TECHNICAL DETAILS




Color: Foggy	Layout:	Pattern: Versailles
--------------	---------	---------------------

1. PRODUCT INFO		2. STRUCTURE	3. PACKAGING	
Species	White European Oak	2-layer Engineered Construction * Solid wood 4 mm ** Plywood *** 		
Finish	UV Silk		BOX	PALLET
Structure	Engineered (2-layer)		2 m ² (21,53 ft ²)	64 m ² (689 ft ²)
Joint	T&G		Dimensions (T _W L):	Dimensions (L _W H):
Bevel	Micro (0,5 mm)		30 x 1010 x 1010 mm	1010 x 1010 x 970 mm
Surface	Light Brush		(2,36''*2,66''*2,66')	(5,31''*2,66''*3,18')
Grade	Select	* High Balance and Stability	Weight:	Weight:
DIMENSIONS		** Saw Cut White European Oak	23 kg (51 lb)	736 kg (1623 lb)
Thickness	15 mm (5/8")	*** Birch water resistant plywood		
Width	1000 mm (3,28')			
Row Length	1000 mm (3,28')			
Shorts	-			

4. FINISH		5. DESCRIPTION	
Sheen \ Gloss	Matte	Name	Select
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	UV cured modified polyurethane-acrylate	Other	
Wear resistance	High	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.	
Scratch resistance	Medium		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	Class 5 (Except blue ink)		
Maintanance	Maintenance free		
Repairability	Easy		

6. TECHNICAL INFORMATION			
Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length



PRODUCT USE

7. INSTALLATION		8. STORAGE & USE	
Level	Glue-down	Air Humidity 40-65%	Temperature +18°C ... +22°C (64°F ... 72°F)
Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.			

9. CARE & MAINTENANCE	10. DESCRIPTIONS & IMAGERY
Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Ruunaoja tn 3, 11415, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: @me_floor_



NO ADDED formaldehyde

