

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Foggy	Layout:	Pattern: Versailles
--------------	---------	---------------------

1. PRODUCT INFO 2. STRUCTURE 3. PACKAGING

Species	White European Oak	2-layer Engineered Construction * Solid wood 4 mm ** Plywood *** * High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood	 BOX 2,232 m2 (21,5 ft2) Dimensions (TWL): 65 x 760 x 760 mm (2,56''*30''*30'') Weight: 29 kg (64 lb)	 PALLET 33,48 m2 (355 ft2) Dimensions (LWH): 780 x 780 x 985 mm (2,6'*2,6'*3,2') Weight: 450 kg (993 lb)
Finish	UV Silk			
Structure	Engineered (2-layer)			
Joint	T&G			
Bevel	Micro (0,5 mm)			
Surface	Light Brush			
Grade	Select			
DIMENSIONS				
Thickness	15 mm (5/8'')			
Width	747 mm (2,45')			
Row Length	747 mm (2,45')			
Shorts	-			

4. FINISH 5. DESCRIPTION

Sheen \ Gloss	Matte	Name	Select
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	UV cured modified polyurethane-acrylate	Other	
Wear resistance	High	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.	
Scratch resistance	Medium		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	Class 5 (Except blue ink)		
Maintanance	Maintenance free		
Repairability	Easy		

6. TECHNICAL INFORMATION		Deviations (EN 13489)	
Characteristics (EN 14342)		Deviation on Thickness	
Formaldehyde emission class	E1; ULEF	Deviation on Width	+/- 0,2 mm
Pentachlorophenol content	None	Height Difference	+/- 0,2 mm
Thermal resistance	0,118 m2 K\W	Cup	<0,2% of width
Thermal conductivity	0,161 W\ (m K)	Bow	<0,5% of length
Fire resistance	Dfl-s1	Spring	<0,1% of length



PRODUCT USE

7. INSTALLATION 8. STORAGE & USE

 Level	 Glue-down	Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.	 Air Humidity 40-65%	 Temperature +18°C ... +22°C (64°F ... 72°F)
-----------	---------------	--	----------------------------	---

9. CARE & MAINTENANCE 10. DESCRIPTIONS & IMAGERY

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.
---	---