

# HARDWOOD FLOORING

## TECHNICAL DETAILS



Color: Foggy	Layout:	Pattern: Versailles
--------------	---------	---------------------

### 1. PRODUCT INFO      2. STRUCTURE      3. PACKAGING

Species	White European Oak	2-layer Engineered Construction *  Solid wood 4 mm ** Plywood ***  * High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood		
Finish	UV Silk			
Structure	Engineered (2-layer)		BOX	PALLET
Joint	T&G		2,56 m2 (28 ft2)	81,92 m2 (882 ft2)
Bevel	Micro (0,5 mm)		Dimensions (TWL): 60 x 810 x 810 mm (2,36"*2,66"*2,66')	Dimensions (LWH): 1620 x 810 x 970 mm (5,31"*2,66"*3,18')
Surface	Light Brush		Weight: 30 kg (67 lb)	Weight: 960 kg (2117 lb)
Grade	Select			
DIMENSIONS				
Thickness	15 mm (5/8")			
Width	800 mm (2,62')			
Row Length	800 mm (2,62')			
Shorts	-			

### 4. FINISH      5. DESCRIPTION

Sheen \ Gloss	Matte	Name	Select
Look	Semi-open pores, wire brushed	Color variation	
Feeling	Transfer warmth of natural wood	Knots	
Type	UV cured modified polyurethane-acrylate	Other	
Wear resistance	High	Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.	
Scratch resistance	Medium		
Slip resistance	50 (SRV dry)		
Resistance to chemical agents	Class 5 (Except blue ink)		
Maintanance	Maintenance free		
Repairability	Easy		

6. TECHNICAL INFORMATION					
Characteristics (EN 14342)				Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF			Deviation on Thickness	+/- 0,2 mm
Pentachlorophenol content	None			Deviation on Width	+/- 0,2 mm
Thermal resistance	0,118 m2 K\W			Height Difference	+/- 0,2 mm
Thermal conductivity	0,161 W\ (m K)			Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length		
		Spring	<0,1% of length		

## PRODUCT USE

### 7. INSTALLATION      8. STORAGE & USE

Level Glue-down	Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.	Air Humidity 40-65%	Temperature +18°C ... +22°C (64°F ... 72°F)
--------------------	--	------------------------	---

### 9. CARE & MAINTENANCE      10. DESCRIPTIONS & IMAGERY

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with.	Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.
---	---

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ  
 Ruunaoja tn 3, 11415, Tallinn, Estonia  
 VAT EE102590311  
 E-mail: info@me-decor.com  
 www.me-floor.com  
 Inst.: @me\_floor\_



NO ADDED formaldehyde

