


HARDWOOD FLOORING

TECHNICAL DETAILS



Color: ME Floor Colors

Layouts:



Patterns: Plank, Chevron, Herringbone

1. PRODUCT INFO		2. STRUCTURE		3. PACKAGING	
Species	White European Oak	2-layer Engineered Construction *			
Finish	UV Silk/ Silk Oxi/ Unfinished				
Structure	Engineered (2-layer)	Solid wood 3-4 mm** Plywood***		BOX	PALLET
Joint	T&G			Cardboard	Stretch-wrapped
Bevel	Micro (4-sides)	* High Balance and Stability ** Saw Cut White European Oak Lamella nominal value variations are normal due to the specific nature of wood and each decor and not considered defects *** Birch water resistant plywood		Dimensions (TWL): depends on product size	Dimensions (LWH): depends on product size
Surface	Sanded/ Brushed/ Cross-Cut			Weight: 12-30 kg	Weight: 600-1400 kg
Grade	Select/ Nature/ Character				
DIMENSIONS					
Thickness	15 mm				
Width	90-300 mm				
Row Length	600-6000 mm				
Shorts	Depends on product				
4. GRADES DESCRIPTION					
Name	Select	Name	Nature	Name	Character
Color variation		Color variation		Color variation	
Knots		Knots		Knots	
Other		Other		Other	
Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.		Nature grade looks pretty clean and organic. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.		Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes	
5. TECHNICAL INFORMATION					
Characteristics (EN 14342)		Deviations (EN 13489)		Wood is a natural material with every piece unique. Variation in color, texture and overall look is normal and unavoidable due to its nature. Like other materials, wood age with time and change in shade on exposure to light. Some difference btw produced floors and reference samples is normal due to this reason.	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	+/- 0,2 mm		
Pentachlorophenol content	None	Deviation on Width	+/- 0,2 mm		
Thermal resistance	0,118 m2 K\W	Height Difference	+/- 0,2 mm		
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width		
Fire resistance	Dfl-s1	Bow	<0,5% of length		
		Spring	<0,1% of length		

PRODUCT USE

6. INSTALLATION		7. STORAGE & USE	
 Level	 Floor Heating	 Glue-down	 Air Humidity 40-65%
Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.			 Temperature +18°C ... +22°C (64°F ... 72°F)
8. CARE & MAINTENANCE		9. DESCRIPTIONS & IMAGERY	
Maintenance of hardwood floors with UV Silk/ Silk Oxi assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.		Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.	

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
 Kopli 27, 10412, Tallinn, Estonia
 VAT EE102590311
 E-mail: info@me-decor.com
 www.me-floor.com
 Inst.: @me_floor_



NO ADDED formaldehyde

