

HARDWOOD FLOORING

TECHNICAL DETAILS



Color: Upon Request

Layout:




Pattern: Plank

1. PRODUCT INFO

Species	White European Oak
Finish	UV Silk/ Silk Oxi/ Unfinished
Structure	Engineered (3-layer)
Joint	T&G/ Click
Bevel	Micro (4-sides)
Surface	Sanded/ Brushed/ Cross-Cut
Grade	Select/ Nature/ Character
DIMENSIONS	
Thickness	14-15 mm
Width	150-240 mm
Row Length	1900-2230 mm
Shorts	occasional

2. STRUCTURE

3-layer Engineered Construction *



* Saw Cut White European Oak 3-4 mm

Lamella nominal value variations are normal due to the specific nature of wood and each decor and not considered defects

** Core & Base

Softwood or Hardwood stabilizing bars with compensation gaps on soft or hardwood stabilizing foundation

3. PACKAGING

BOX	PALLET
Cardboard	Stretch-wrapped
Dimensions (TWL): depends on product size	Dimensions (LWH): depends on product size
Weight: 20-30 kg	Weight: 600-1400 kg

4. GRADES DESCRIPTION


Name	Select	Name	Nature	Name	Character
Color variation		Color variation		Color variation	
Knots		Knots		Knots	
Other		Other		Other	
Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.		Nature grade looks pretty clean and organic. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.		Character Grade creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes	

5. TECHNICAL INFORMATION

Characteristics (EN 14342)	Deviations (EN 13489)	Wood is a natural material with every piece unique. Variation in color, texture and overall look is normal and unavoidable due to its nature. Like other materials, wood age with time and change in shade on exposure to light. Some difference btw produced floors and reference samples is normal due to this reason.
Formaldehyde emission class	E1; ULEF	
Pentachlorophenol content	None	
Thermal resistance	0,104 m2 K\W	
Thermal conductivity	0,144 W\m K	
Fire resistance	Dfl-s1	
	Deviation on Thickness	+/- 0,2 mm
	Deviation on Width	+/- 0,2 mm
	Height Difference	+/- 0,2 mm
	Cup	<0,2% of width
	Bow	<0,5% of length
	Spring	<0,1% of length

PRODUCT USE


6. INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Semifloating installation as well.

Applicable above, on and below ground level. Suitable for underfloor heating.

7. STORAGE & USE



Air Humidity
40-65%



Temperature
+18°C ... +22°C
(64°F ... 72°F)

8. CARE & MAINTENANCE

Maintenance of hardwood floors with UV Silk/ Silk Oxi assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.

9. DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

Technical or material improvements that do not affect the product's decor, dimensions, warranty or performance may be introduced unilaterally.



ME Decor Group OÜ
Kopli 27, 10412, Tallinn, Estonia
VAT EE102590311
E-mail: info@me-decor.com
www.me-floor.com
Inst.: [@me_floor_](https://www.instagram.com/me_floor_)



nwfa
compliant

NO ADDED
formaldehyde

