

HARDWOOD FLOORING



TECHNICAL DETAILS

Notes:

Pattern: Plank



Color: Natural Unfinished

PRODUCT INFO


Species	White European Oak
Finish	Unfinished
Structure	Engineered (2-layer)
Joint	T&G
Bevel	Micro (0,5 mm)
Surface	Sanded (120 grit)
Grade	Nature
DIMENSIONS	
Thickness	15 mm (5/8")
Width	240 mm (9,45")
Row Length	2200 mm (7,2')
Shorts	25%

PACKAGING

BOX	36 kg (79 lb)	3,168 m ² (34 ft ²)
	95 mm (3,75")	250 mm (9,8")
PALLET	1470 kg (3241 lb)	126,72 m ² (1364 ft ²)
	1100 mm (3,6')	2250 mm (7,4')

STRUCTURE

2-layer Engineered Construction *



* High Balance and Stability
 ** Saw Cut White European Oak
 *** Birch water resistant plywood

FINISH

Sheen \ Gloss	n/a
Look	Smooth
Feeling	Transfer warmth of natural wood
Type	Unfinished
Wear resistance	n/a
Scratch resistance	n/a
Slip resistance	n/a
Resistance to chemical agents	n/a
Maintenance	n/a
Repairability	Easy

Description

natural wood	small burls
authentic natural	nice texture
mild	color variation
moderate	some sapwood
medullary spots	restored knots

Nature grade looks pretty clean in 240 mm width. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.

TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length


PRODUCT USE

INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Semi-floating installation as well. Applicable above, on and below ground level. Suitable for underfloor heating.

STORAGE & USE



Air Humidity 40-65%
 Temperature +18°C ... +22°C (64°F ... 72°F)

CARE & MAINTANENCE

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed.

DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

