


HARDWOOD FLOORING

TECHNICAL DETAILS

Notes:

Pattern: Herringbone



Color: Natural Unfinished

PRODUCT INFO

Species	White European Oak
Finish	Unfinished
Structure	Solid
Joint	T&G
Bevel	Micro (0,5 mm)
Surface	Sanded (120 grit)
Grade	Select/Nature/Rustic
DIMENSIONS	
Thickness	16 mm (5/8")
Width	68 mm (2,68")
Row Length	270 mm (10,6")
Angle	90


PACKAGING

BOX	4 kg (8,8 lb)	0,367 m ² (3,95 ft ²)
	160 mm (6,3")	136 mm (5,4")
PALLET	672 kg (1482 lb)	61,69 m ² (664 ft ²)
	1120 mm (3,67')	800 mm (2,62')
		1200 mm (3,94')

STRUCTURE

Solid Construction*

Solid wood
Wear Layer 6 mm



*White European Oak

FINISH

Sheen \ Gloss	n/a
Look	Smooth
Feeling	Transfer warmth of natural wood
Type	Unfinished
Wear resistance	n/a
Scratch resistance	n/a
Slip resistance	n/a
Resistance to chemical agents	n/a
Maintenance	n/a
Repairability	Easy

DESCRIPTION

Select: Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.

Nature: Looks pretty clean and organic. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.

Rustic: Creates an effect of antique wood and emphasizes authentic natural oak texture. Planks may contain diverse color variation, sapwood, unlimited burls, brown streaks, tight knots and properly filled open knots, warm holes as well as other imperfections.

TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m ² K/W	Height Difference	0,2 mm
Thermal conductivity	0,161 W/(m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length


PRODUCT USE

INSTALLATION



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above and on ground level.

STORAGE & USE



Air Humidity 40-65%
Temperature +18°C ... +22°C
(64°F ... 72°F)

CARE & MAINTANENCE

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed.

DESCRIPTIONS & IMAGERY

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.