HARDWOOD FLOORING



TECHNICAL DETAILS

Notes: Pattern: Herringbone Color: Natural Unfinished

PRODUCT INFO		PACKA	GING	STRUCTURE
Species Finish Structure Joint Bevel	White European Oak Unfinished Engineered (2-layer) T&G Micro (0,5 mm)	вох	15 kg (33 lb) 1,318 m²(14 ft²) 125 mm\$ 280 mm (5") 615 mm (2')	2-layer Engineered Construction * Solid wood 4 mm ** Plywood ***
Surface Grade DIMENSIONS Thickness Width Row Length Angle	Sanded (120 grit) Select 15 mm (5/8") 90 mm (3,55") 610 mm (23,6') 90	PALLET	945 kg (2083 lb) 84,352 m² (908 ft²) 1100 mm (3,6¹) 1230 mm (4¹)	*High Balance and Stability ** Saw Cut White European Oak *** Water resistant plywood

FINISH					
Sheen \ Gloss	n/a				
Look	Smooth				
Feeling	Transfer warms of natural wood				
Туре	Unfinished				
Wear resistance	n/a				
Scratch resistance	n/a				
Slip resistance	n/a				
Resistance to chemical agents	n/a				
Maintenance	n/a				
Repairability	Easy				

natural wood			rare knots		
even tex	kture			perfect look	
uniform	slight color variation				
clean plani	ks	minimal sapwood			
smooth s	urf	face	Ş	selected grain	

DESCRIPTION

Product clean look is created by minimalistic natural wood color variation, occasional small knots up to 10mm, as well as rare light sapwood.

TECHNICAL INFORMATION

Characteristics (EN 14342)		Deviations (EN 13489)		
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm	
Pentachlorophenol content None		Deviation on Width	0,2 mm	
Thermal resistance 0,118 m2 K\W		Height Difference	0,2 mm	
Thermal conductivity 0,161 W\(m K)		Cup	<0,2% of width	
Fire resistance	Dfl-s1	Bow	<0,5% of length	
		Spring	<0,1% of length	



PRODUCT USE

INSTALLATION STORAGE & USE







Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.

Applicable above, on and below ground level. Suitable for underfloor heating.





Air Humidity Temperature 40-65% +18°C ... +22°C (64°F ... 72°F)

CARE & MAINTANENCE

Maintenance of hardwood floors depends on the applied finish. Flooring assumes daily cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed.

Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.

DESCRIPTIONS & IMAGERY









