

HARDWOOD FLOORING

TECHNICAL DETAILS

Notes:	Pattern: Herringbone	Color: Linen
---------------	-----------------------------	---------------------

PRODUCT INFO		PACKAGING		STRUCTURE
Species	White European Oak	BOX 		2-layer Engineered Construction *
Finish	UV Silk			
Structure	Engineered (2-layer)			
Joint	T&G			
Bevel	Micro (0,5 mm)			
Surface	Light Brush	PALLET 		* High Balance and Stability ** Saw Cut White European Oak *** Birch water resistant plywood
Grade	Nature			
DIMENSIONS				
Thickness	15 mm (5/8")			
Width	125 mm (5")			
Row Length	600 mm (23,6")			
Angle	90			

FINISH		DESCRIPTION										
Sheen \ Gloss	Matte	<table border="1"> <tr> <td>natural wood</td> <td>small burls</td> </tr> <tr> <td>authentic natural</td> <td>nice texture</td> </tr> <tr> <td>mild</td> <td>color variation</td> </tr> <tr> <td>moderate</td> <td>some sapwood</td> </tr> <tr> <td>medullary spots</td> <td>restored knots</td> </tr> </table> <p>Nature grade looks pretty clean and organic. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.</p>	natural wood	small burls	authentic natural	nice texture	mild	color variation	moderate	some sapwood	medullary spots	restored knots
natural wood	small burls											
authentic natural	nice texture											
mild	color variation											
moderate	some sapwood											
medullary spots	restored knots											
Look	Semi-open pores, wire brushed											
Feeling	Transfer warms of natural wood											
Type	UV cured modified polyurethane-acrylate											
Wear resistance	High											
Scratch resistance	Medium											
Slip resistance	50 (SRV dry)											
Resistance to chemical agents	Class 5 (Except blue ink)											
Maintenance	Maintenance free											
Repairability	Easy											

TECHNICAL INFORMATION			
Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m2 K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\m K	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

PRODUCT USE

INSTALLATION	STORAGE & USE
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and above ground level.</p>	<p>Air Humidity 40-65% Temperature +18°C ... +22°C (64°F ... 72°F)</p>

CARE & MAINTANENCE	DESCRIPTIONS & IMAGERY
<p>Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with oil.</p>	<p>Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.</p>