



HARDWOOD FLOORING



Notes:	Pattern: Chevron 	Color: White Snow
---------------	---	--------------------------

PRODUCT INFO		PACKAGING		STRUCTURE
Species	White European Oak	BOX	13 kg (29 lb)	2-layer Engineered Construction Solid wood 4 mm Plywood** 
Finish	UV Silk		1,17 m ² (13 ft ²)	
Structure	Engineered (2-layer)		125 mm (5")	
Joint	T&G		260 mm (10,25")	
Bevel	Micro (0,5 mm)		725 mm (2,4')	
Surface	Light Brush	PALLET	839 kg (1849 lb)	*High Balance and Stability **Saw Cut White European Oak ***Birch water resistant plywood
Grade	Nature		74,88 m ² (806 ft ²)	
DIMENSIONS			1100 mm (3,6')	
Thickness	15 mm (5/8")		1480 mm (4,9')	
Width	125 mm (5")		1070 mm (3,5')	
Row Length	585 mm (23')			
Angle	45			

FINISH		DESCRIPTION										
Sheen \ Gloss	Semi-Matte	<table border="1"> <tr><td>natural wood</td><td>small burls</td></tr> <tr><td>authentic natural</td><td>nice texture</td></tr> <tr><td>mild</td><td>color variation</td></tr> <tr><td>moderate</td><td>some sapwood</td></tr> <tr><td>medullary spots</td><td>restored knots</td></tr> </table> <p>Nature grade looks nice in Chevron Pattern. Though, any natural wood might vary. Surface allows reasonable burls, light brown streaks, some restored knots, properly filled open checks and worm holes. Slight imperfections in face work (torn grain) and burns are admitted.</p> 	natural wood	small burls	authentic natural	nice texture	mild	color variation	moderate	some sapwood	medullary spots	restored knots
natural wood	small burls											
authentic natural	nice texture											
mild	color variation											
moderate	some sapwood											
medullary spots	restored knots											
Look	Semi-open pores, wire brushed											
Feeling	Transfer warms of natural wood											
Type	UV cured modified polyurethane-acrylate											
Wear resistance	High											
Scratch resistance	Medium											
Slip resistance	Not rated											
Resistance to chemical agents	50 (SRV dry)											
Maintenance	Maintenance free											
Repairability	Easy											

TECHNICAL INFORMATION			
Characteristics (EN 14342)		Deviations (EN 13489)	
Formaldehyde emission class	E1; ULEF	Deviation on Thickness	0,2 mm
Pentachlorophenol content	None	Deviation on Width	0,2 mm
Thermal resistance	0,118 m ² K\W	Height Difference	0,2 mm
Thermal conductivity	0,161 W\ (m K)	Cup	<0,2% of width
Fire resistance	Dfl-s1	Bow	<0,5% of length
		Spring	<0,1% of length

INSTALLATION

 <p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for underfloor heating.</p>	STORAGE & USE  <p>Air Humidity 40-65% Temperature +18°C ... +22°C (64°F ... 72°F)</p>
---	--

CARE & MAINTENANCE <p>Maintenance of hardwood floors with UV Silk assumes normal (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with floor cleaner. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc. should be periodically renewed with oil.</p>	DESCRIPTIONS & IMAGERY <p>Flooring colors displayed in digital platforms may vary according to the color settings of the monitor you are using.</p>
--	---